Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for driving a display device having a display panel, the method comprising:

confirming whether display data applied to the display panel are uniformly maintained for a predetermined time;

dividing the display panel into at least two <u>pixel</u> block sets when the display data are uniformly maintained for a predetermined time; and

sequentially performing screen save modes for each <u>pixel</u> block set, wherein the screen save modes apply screen save mode data, which turns pixels within the <u>pixel</u> block set on or off sequentially or inverts the display data, to the block set.

(Previously Presented) The method of claim 1, further comprising:
 releasing the screen save modes when the display data are changed during the
 screen save modes; and

displaying the display data only on the display panel.

- 3. (Previously Presented) The method of claim 1, further comprising displaying the display data on the display panel without performing the screen save modes when the display data are changed without being uniformly maintained for a predetermined time.
- 4. (Currently Amended) The method of claim 1, wherein the <u>pixel</u> block <u>sets</u> for the screen save modes is any one of a column block consisting of at least one pixel column, a row block consisting of at least one pixel row, and a pixel block consisting of N1 x M1 (N1 and M1 are positive integers) pixels.
- 5. (Original) The method of claim 1, wherein the screen save mode data are inverse data of the display data.
 - 6. (Canceled).
- 7. (Currently Amended) A method for driving a display device having a display panel, the method comprising:

confirming whether display data applied to the display panel are uniformly maintained for a predetermined time;

configuring the display panel into at least one pixel column block set when the display data are uniformly maintained for a predetermined time; and

sequentially performing screen save modes by on each pixel column block set, wherein the screen save modes apply screen save mode data, which turns pixels within the pixel column block set on or off sequentially or inverts the display data, to the pixel column block set.

- 8. (Canceled).
- 9. (Previously Presented) The method of claim 7, further comprising:
 releasing the screen save modes when the display data are changed during the
 screen save modes; and

displaying the display data only on the display panel.

10. (Currently Amended) A method for driving a display device having a display panel, the method comprising:

confirming whether display data applied to the display panel are uniformly maintained for a predetermined time;

configuring the display panel into at least one pixel row block set when the display data are uniformly maintained for a predetermined time; and

sequentially performing screen save modes by on each pixel row block set, wherein the screen save modes apply screen save mode data, which turns pixels within the pixel row block set on or off sequentially or inverts the display data, to the pixel row block set.

11. (Previously Presented) The method of claim 10, further comprising:

releasing the screen save modes when the display data are changed during the

screen save modes; and

displaying the display data only on the display panel.

12. (Canceled).

13. (Currently Amended) A method for driving a display device having a display

panel, the method comprising:

confirming whether display data applied to the display panel are uniformly

maintained for a predetermined time;

configuring the display panel into at least one N1 x M1 (N1 and M1 are

positive integers) pixel block set when the display data are uniformly maintained for a

predetermined time; and

8

sequentially performing screen save modes by on each N1 x M1 pixel block set, wherein the screen save modes apply screen save mode data, which turns pixels within the N1 x M1 pixel block set on or off sequentially or inverts the display data, to the N1 x M1 pixel block set.

14. (Previously Presented) The method of claim 13, further comprising:

releasing the screen save modes when the display data are changed during the

screen save modes; and

displaying the display data only on the display panel.

15. (Canceled).

16. (Original) The method of claim 13, wherein the N1 x M1 pixel block has a

size of 11 x 12 pixels or 6 x 12 pixels.

17-23. (Canceled).

24. (Previously Presented) The method of claim 7, wherein configuring the display

panel comprises dividing the display panel into at least two pixel column block sets.

9

- 25. (Previously Presented) The method of claim 10, wherein configuring the display panel comprises dividing the display panel into at least two pixel row block sets.
- 26. (Previously Presented) The method of claim 13, wherein configuring the display panel comprises dividing the display panel into at least two N1 x M1 pixel block sets.
- 27. (Currently Amended) A method for driving a display panel, the method comprising:

confirming whether display data applied to the display panel are uniformly maintained for a predetermined time;

dividing the display panel into at least two blocks one pixel block set when the display data are uniformly maintained for a predetermined time; and

sequentially performing screen save modes that apply the display data and screen save mode data to each of the blocks pixel blocks sets, wherein the screen save mode data are inverse data of the display data.

28. (Currently Amended) The method of claim 1, wherein the screen save mode data turns all pixels within the <u>pixel</u> block set on or off sequentially.